

Control Zone Kits

Models: CZK100-30, CZK100-30F, CZK100-40, CZK100-40F



FEATURES

- 1" reversed flow valve with PRYF pressure regulating filter
- Durable glass filled nylon assembly
- On/off manual bleed switch for easy operation during installation and maintenance
- 4 bolt stainless steel cover with brass inserts for easy maintenance
- Diaphragm's self cleaning ports constantly flex, inhibiting sand and silt from blocking valve action
- High efficiency solenoid with stainless steel actuator. Compatible with two-wire systems
- EZ-Flush cap on PRYF filter for easy flushing during installation
- Universal Smart-Loc fitting on discharge of 30 psi models. Compatible with 16-18mm tubing

SPECIFICATIONS

- Flow: 30 psi models = .2-5 gpm (12 to 300 gph), 40 psi models = .2-15 gpm (12 to 900 gph)
- Inlet pressure: 15 to 150 psi (1 to 10.3 bar)
- Filtration: 200 mesh stainless steel (75 micron)
- Regulated Pressure: 30 psi and 40 psi units
- Electrical specifications: Inrush: 9.48 VA, Holding: 5.11 VA

Model Nomenclature

CZK	100	-	30/40	F
Control Zone Kit	1" Valve		Discharge PSI	Flow Control