

TECHNICAL SPECIFICATIONS

SEWER AND DRAIN PIPE CORRUGATED ADAPTER

MEETS ASTM STANDARDS: PVC-ASTM D-3034, D-2729 STYRENE—D-2852 MOLDED IN THE USA MADE OF POLYETHYLENE. FITS THE FOLLOWING PIPE FITTINGS: SDR-35, SDR-26, TRIPLE WALL, & ASTM D-2729 PIPE, FITS SINGLE WALL CORRUGATED PIPE SPT X HUB CONNECTION

SPT = SPIGOT CONNECTION



MATERIAL	PART NUMBER	A (INCHES)	B (INCHES)	C SPIGOT INSIDE DIAMETER (INCHES)	D HUB INSIDE DIAMETER (INCHES)	WEIGHT (LBS)
POLYETHYLENE	351	1.96	3.99	2.68	3.75	0.10
	451	2.09	4.41	3.38	4.82	0.15
	651	2.69	6.35	5.37	7.10	0.25

NOTE: NOT FOR USE IN PRESSURIZED WATER SYSTEMS. 5 P.S.I. MAXIMUM DOES NOT FIT SCHEDULE 40 PIPE

851 N. Harvard Avenue Lindsay, CA 93247 800-726-1994



Visit ndspro.com for specs, detail drawings, and case studies

