

TECHNICAL SPECIFICATION


SLIP X SLIP CLEAR SPRING CHECK VALVE

RATED @125 PSI STATIC PRESSURE @ 72°F MOLDED IN THE USA MADE OF PVC TYPE I MATERIAL EPDM GASKET STAINLESS STEEL SPRING

IPS SLIP X IPS SLIP

IPS—IRON PIPE SIZE (SAME AS SCH. 40 PIPE)





PART #					
OPEN PSI	FULL OPEN PSI				

PART NUMBER				٨	D	WEIGHT	IPS CONNECTION
1/2# SF	PRING	2# SPRING		A	В	(LBS)	SIZE
1011C10 1.53 PSI 4.79 PSI		N/A		5.61"	2.31"	0.35	1" IPS
1011C12		1012C12		6.4022	2.100	0.77	1.1/47 IDG
0.69 PSI	1.50 PSI	1.00 PSI	3.32 PSI	6.40"	3.18"	0.75	1 1/4" IPS
1011C15		N/A		6.82"	3.17"	0.80	1 1/2" IPS
0.58 PSI	1.30 PSI	IN/A		0.82	3.17	0.80	1 1/2 11 3
1011C20		N/A		7.46"	4.06"	1.30	2" IPS
0.86 PSI	3.72 PSI	IN/A		7.40	4.00	1.30	۷ ۱۲۵

NOTE: VALVE IS CONSIDERED OPEN WHEN SPRING IS COMPRESSED 1/8". FULL OPEN IS COMPLETE COMPRESSION OF SPRING. FOR 1/2" AND 3/4" VALVES FULL OPEN IS APPROXIMATELY 1/8".

