

Pro-Span[®] Compact[™] **Expansion Repair Coupling**

Make Fast Pipe Repairs in the Tightest Spaces

The Pro-Span® Compact™ expansion repair coupling is engineered to work in cramped and confined spaces to replace broken pipe or provide an extension for a section of pipe that is too short. Ideal for use in cramped areas but works well for pipe repair of various lengths.

NDS Pro-Span Compact repair coupling is the preferred choice of leading irrigation, plumbing, and drainage contractors. Every NDS product is engineered for performance, durability, and ease of installation. No product is added to our line without meeting extensive testing and research requirements.



Time and Labor Savings

- · Requires less excavating to access the broken pipe / leak that needs repair
- · Telescoping design bridges the gap between the two ends of cut PVC pipe, reducing time spent measuring
- · Easy-Grip handle provides a firm grip for wet and muddy hands
- · Contractors claim shorter repair coupling reduces pipe cutting and waste
- · Pro-Span Compact piston and space between O-Ring & body are loose when relaxed to help adjust coupling to a functional length
- · Dual O-Ring safety design stops the leak before it starts
- · Saves time during installation



Compact Design

- · Up to 10% shorter than competitive products
- · 10-25% shorter than the Pro-Span® Expansion Repair Coupling
- · Length is adjustable and locks in place for ease of installation
- · Install requirements are molded onto Pro-Span Compact; scan included QR code for instructions

Smart Engineering

- · Patented Grip-Lock technology prevents the piston from spinning when inserting onto pipe
- · Spin weld cap design ensures a water-tight seal
- · True-Cut feature automatically positions the piston seals and eliminates potential joint-separation stress
- · 1-year product defect warranty

PART NO.	DESCRIPTION	COMPRESSED LENGTH	MAX OPERATION LENGTH	SPECIFICATIONS
118-05C 118-07C 118-10C 118-12C 118-15C 118-20C	Pro-Span® Compact™ 1/2 in. Expansion Repair Coupling Pro-Span® Compact™ 3/4 in. Expansion Repair Coupling Pro-Span® Compact™ 1 in. Expansion Repair Coupling Pro-Span Compact™ 1-1/4 in. Expansion Repair Coupling Pro-Span® Compact™ 1-1/2 in. Expansion Repair Coupling Pro-Span® Compact™ 2 in. Expansion Repair Coupling	4-3/4 in. 5-1/8 in. 5-3/4 in. 6-1/4 in. 7 in. 7-1/2 in.	7-3/8 in. NSF 8-1/4 in. Rat	de of PVC F-61/IAPMO ed @200 PSI tic Pressure 2°F

NDS-ss-pro-span-compact-expansion-repair-coupling-en.pdf

SCAN TO LEARN MORE