

Universal Spray-to-Drip Conversion Kit and Pop-Up Sprinkler Cap

APPLICATION

- Converts an existing sprinkler system into a drip irrigation system
- Universal Conversion Kit converts a single sprinkler head into a drip zone
- Universal Pop-Up Sprinkler Cap closes off an existing spray head

KIT FEATURES

- Kit Includes a 30 PSI filter regulator, universal adapter with two Smart Loc™ multidiameter outlets, and an end cap
- Designed to retrofit most manufacturers' pop-up spray head bodies
- Adapter fitting has a swivel inlet that prevents tubing from kinking or bending
- End cap closes one outlet if needed
- Filter regulator and Smart Loc™ multidiameter fittings are made of acrylonitrile butadiene styrene (ABS)
- Treated with UV inhibitors to prevent fading and cracking
- Removable 150-mesh stainless steel screen blocks particulates that can potentially clog and damage emitters
- Use with the Universal Pop-Up Sprinkler Cap to close off spray heads that are no longer necessary

OPERATING RANGE

- Flow rate: up to 6.5 GPM
- Outlet pressure: 30 PSI
- Inlet pressure: 15-70 PSI

SPECIFICATIONS

- 1/2 in. FPT inlet installs on 1/2 in. risers
- Smart Loc™ multidiameter outlets connect to supply tubing or dripline of multiple sizes: 16mm, 17mm, and 18mm

CAP FEATURES

- Two-piece design is compatible with most manufacturers' spray heads
- Eliminates need to remove the entire sprinkler
- Cap is made of acrylonitrile butadiene styrene (ABS); Stopper is made of polypropylene
- Treated with UV inhibitors to prevent fading and cracking

WARRANTY

- Limited one-year warranty



FR2 17-710

Part Number	Description
FR2 17-710	Universal Spray-to-Drip Conversion Kit
CAP POP/5	Universal Pop-Up Sprinkler Cap (5-Pack)
CAP POP/25	Universal Pop-Up Sprinkler Cap (25-Pack)

Conversion Kit		Max Flow (GPM)
FR2 17-710		6.5
Maximum Total Feet of Tubing		
0.6 GPH 12 in.	0.6 GPH 18 in.	0.6 GPH 24 in.
650 ft.	970 ft.	1,300 ft.
0.9 GPH 12 in.	0.9 GPH 18 in.	0.9 GPH 24 in.
433 ft.	650 ft.	866 ft.