



## SPEE-D CHANNEL 24" WAVE DECORATIVE GRATE



**Part # (Color):** 253 (BLACK) 253S (SAND) 253GY (GRAY)  
**Material:** HDPE (High Density Polyethylene)  
**Weight:** 1.84 lbs  
**Fits:** Spee-D #400, #400-10  
**Dimension:** 4.42 Inches WIDE x 24 Inches LONG x 0.925 inches HIGH  
**Grate Opening:** 0.25 inches max. along length  
 0.88 inches max transverse  
**Open Surface Area:** 7.78 in<sup>2</sup>/foot

- ADA COMPLIANT
- HEEL PROOF

#### Load Recommendation

-  **Class B**
- Loads of 61-175 psi.
  - Recommended for medium-duty pneumatic tire traffic, autos and light trucks at speeds less than 20 m.p.h.

#### Head Pressure (inches) - Flow Rate per foot:

0.5 inch - 24 GPM/foot  
 1 inch - 34 GPM/foot

#### ADA Compliance

NDS provides a wide selection of grates that are compliant with the Americans with Disabilities Act. The ADA Accessibility Guidelines For Buildings and Facilities Section 4.5.4 specifies that ground and floor grates "shall have spaces no greater than 1/2 in (13 mm) wide in one direction."

We are pleased to provide grates that comply with these requirements, so that no individual need be limited from accessing the area safely and confidently.

To see if a grate is ADA compliant, please check the description of the product in our NDS Drainage Catalog: products that meet these requirements are marked "ADA compliant."

Like to find out more about ADA compliance and NDS? Send us your question and we'd be happy to help.

**NDS Screws #829** (FH #6 x 1-1/4")  
 Stainless steel, Philips flat head







Rev 03/05/24





**NDS**<sup>TM</sup>  
WE PUT WATER IN ITS PLACE

# TECHNICAL SPECIFICATIONS



851 N. Harvard Avenue  
Lindsay, CA 93247  
800-726-1994  
nds@ndspro.com



Visit [ndspro.com/decorativegrates](https://ndspro.com/decorativegrates) for specs,  
detail drawings, and case studies



**NDS**<sup>®</sup>  
WE PUT WATER IN ITS PLACE